



**EAN:** 4013288113924

**Part number:** 05074739001

**Article number:** 7440/41/42

**Size:** 255x210x62 mm

**Weight:** 1145 g

**Country of origin:** CZ

**Customs tariff number:** 82079030

- Kraftform torque screwdriver set
- Suitable for bits with 1/4" hex head drive
- With Hex-Plus, TORX® and TORX PLUS® bits
- In a stable case

Wera torque screwdriver set. Two high precision torque screwdrivers with variable torque settings. One torque screwdriver with Kraftform pistol handle for the transfer of especially high torque; multi-component for high working speeds and particularly ergonomic screwdriving. Simple adjustment of the required torque value without any special tools. Easy-to-read scale value. Rapidaptor quick-release technology for rapid bit change. Unlimited torque to loosen seized screws. Multi-component Kraftform handle with hard and soft zones for high working speeds, whilst being easy on the hand. Includes a bit assortment in a high quality and stable plastic case.



#### Web link

[https://products.wera.de/en/torque\\_tools\\_series\\_7400\\_kraftform\\_torque\\_screwdrivers\\_variable\\_torque\\_adjustment\\_models\\_7440\\_41\\_42.html](https://products.wera.de/en/torque_tools_series_7400_kraftform_torque_screwdrivers_variable_torque_adjustment_models_7440_41_42.html)

Wera - 7440/41/42  
05074739001 - 4013288113924

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

#### Adjustable Torque Screwdrivers



Wera's adjustable torque screwdrivers allow variable torque settings with maximum precision and ensure that the user gets the very best results in the familiar Wera design with superior ergonomics.

#### Simple setting



Simple setting of the required torque by hand.

#### Easy-to-read



Easy-to-read scale value.

#### Measurement accuracy



Measurement accuracy is  $\pm 6\%$  (article 1430:  $\pm 10\%$ ) in accordance with the standard DIN EN ISO 6789. Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

#### Versatile




Rapidaptor technology makes the tool adaptable since bits and sockets can be exchanged rapidly.

#### Rapid-in and self-lock



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

#### Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

#### Web link

[https://products.wera.de/en/torque\\_tools\\_series\\_7400\\_kraftform\\_torque\\_screwdrivers\\_variable\\_torque\\_adjustment\\_models\\_7440\\_41\\_42.html](https://products.wera.de/en/torque_tools_series_7400_kraftform_torque_screwdrivers_variable_torque_adjustment_models_7440_41_42.html)

Wera - 7440/41/42  
05074739001 - 4013288113924

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

Series 7400 Kraftform Torque Screwdrivers - Variable torque adjustment models

Set contents:

Series 7400 Kraftform adjustable torque screwdrivers (0.1-3.0 Nm) with Rapidaptor quick-release chuck, 7440 x 0.3-1.2 Nm



|             |    |                   |
|-------------|----|-------------------|
| 05074700001 | 1x | 7440 x 0.3-1.2 Nm |
| 05074701001 | 1x | 7441 x 1.2-3.0 Nm |

Series 7400 Kraftform pistol handle, adjustable torque screwdrivers (3.0-8.8 Nm) with Rapidaptor quick-release chuck, 7442 x 3.0-6.0 Nm



|             |    |                   |
|-------------|----|-------------------|
| 05074702001 | 1x | 7442 x 3.0-6.0 Nm |
|-------------|----|-------------------|

867/1 TZ TORX® bits, TX 6 x 25 mm



|             |    |               |
|-------------|----|---------------|
| 05066301001 | 1x | TX 6 x 25 mm  |
| 05066302001 | 1x | TX 7 x 25 mm  |
| 05066303001 | 1x | TX 8 x 25 mm  |
| 05066304001 | 1x | TX 9 x 25 mm  |
| 05066305001 | 1x | TX 10 x 25 mm |
| 05066308001 | 1x | TX 15 x 25 mm |
| 05066310001 | 1x | TX 20 x 25 mm |
| 05066312001 | 1x | TX 25 x 25 mm |
| 05066315001 | 1x | TX 30 x 25 mm |

867/1 IP TORX PLUS® bits, 6 IP x 25 mm



|             |    |               |
|-------------|----|---------------|
| 05066274001 | 1x | 6 IP x 25 mm  |
| 05066276001 | 1x | 7 IP x 25 mm  |
| 05066278001 | 1x | 8 IP x 25 mm  |
| 05066279001 | 1x | 9 IP x 25 mm  |
| 05066280001 | 1x | 10 IP x 25 mm |
| 05066282001 | 1x | 15 IP x 25 mm |
| 05066284001 | 1x | 20 IP x 25 mm |
| 05066286001 | 1x | 25 IP x 25 mm |
| 05066288001 | 1x | 30 IP x 25 mm |

840/1 Z bits, 2 x 25 mm



|             |    |             |
|-------------|----|-------------|
| 05056305001 | 1x | 2 x 25 mm   |
| 05056310001 | 1x | 2.5 x 25 mm |
| 05056315001 | 1x | 3 x 25 mm   |
| 05056320001 | 1x | 4 x 25 mm   |
| 05056325001 | 1x | 5 x 25 mm   |
| 05056330001 | 1x | 6 x 25 mm   |

Web link

[https://products.wera.de/en/torque\\_tools\\_series\\_7400\\_kraftform\\_torque\\_screwdrivers\\_variable\\_torque\\_adjustment\\_models\\_7440\\_41\\_42.html](https://products.wera.de/en/torque_tools_series_7400_kraftform_torque_screwdrivers_variable_torque_adjustment_models_7440_41_42.html)

Wera - 7440/41/42  
05074739001 - 4013288113924

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)