

Shield-Kon® shield termination system

Connector inner and outer sleeves

—
01 Non-insulated
inner sleeve – GSB

—
02 Non-insulated
outer sleeve – GSC

Stay grounded with easy-to-install connectors!

- Hard bronze inner sleeve is installed under braid
- Length $\frac{5}{16}$ "
- Tin plated per MIL-T-10727A

- Soft bronze outer sleeve slips over the braid and ground wire
- Length $\frac{1}{4}$ "
- Tin plated per MIL-T-10727A



01

Inner sleeves

Cat. no.	Color code	Dimensions (in.)		Military spec. no.	Std. pkg.
		I.D.	O.D.		
GSB046	Gray	0.046	0.075	21981-046	1,000
GSB058	Yellow	0.058	0.083	21981-058	1,000
GSB063	Red	0.063	0.088	21981-063	1,000
GSB071	Green	0.071	0.096	21981-071	1,000
GSB080	Blue	0.080	0.103	21981-080	1,000
GSB090	Orange	0.090	0.113	21981-090	1,000
GSB096	Purple	0.096	0.119	21981-096	1,000
GSB101	Yellow	0.101	0.124	21981-101	1,000
GSB109	Red	0.109	0.131	21981-109	1,000
GSB115	Gray	0.115	0.146	21981-115	1,000
GSB124	Green	0.124	0.145	21981-124	1,000
GSB128	Gray	0.128	0.152	21981-128	1,000
GSB134	Orange	0.134	0.156	21981-134	1,000
GSB149	Blue	0.149	0.179	21981-149	1,000
GSB156	Red	0.156	0.193	21981-156	1,000
GSB165	Gray	0.165	0.194	21981-165	1,000
GSB175	Green	0.175	0.215	21981-175	1,000
GSB187	Yellow	0.187	0.227	21981-187	1,000
GSB194	Blue	0.194	0.226	21981-194	1,000
GSB205	Orange	0.205	0.245	21981-205	1,000
GSB219	Gray	0.219	0.250	21981-219	1,000
GSB225	Yellow	0.225	0.256	21981-225	1,000
GSB232	Red	0.232	0.263	21981-232	1,000
GSB250	Green	0.250	0.281	21981-250	1,000
GSB261	Blue	0.261	0.297	21981-261	1,000
GSB266	Gray	0.266	0.297	21981-266	1,000
GSB275	Orange	0.275	0.306	21981-275	1,000
GSB281	Yellow	0.281	0.331	21981-281	1,000
GSB287	Gray	0.287	0.327	21981-287	1,000
GSB297	Red	0.297	0.335	21981-297	1,000
GSB312	Purple	0.312	0.362	21981-312	1,000
GSB348	Orange	0.348	0.400	21981-348	1,000
GSB375	Blue	0.375	0.406	21981-375	1,000

Order multiple is standard package.



02

Outer sleeves

Cat. no.	Color code	Dimensions (in.)		Tools		Military spec. no.	Std. pkg.
		I.D.	O.D.	Die nos. for WT440/ WT540*	Die nos. for 11901A		
GSC101	Gray	0.101	0.124	4419	11989	21980-101	1,000
GSC128	Blue	0.128	0.152	4400	11970	21980-128	1,000
GSC149	Purple	0.149	0.179	4401	11971	21980-149	1,000
GSC156	Yellow	0.156	0.193	4402	11972	21980-156	1,000
GSC175	Blue	0.175	0.215	4403	11973	21980-175	1,000
GSC187	Orange	0.187	0.227	4406	11976	21980-187	1,000
GSC194	Red	0.194	0.226	4406	11976	21980-194	1,000
GSC199	Gray	0.199	0.235	4406	11976	21980-199	1,000
GSC205	Yellow	0.205	0.245	4408	11978	21980-205	1,000
GSC219	Green	0.219	0.250	4408	11978	21980-219	1,000
GSC225	Purple	0.225	0.256	4409	11979	21980-225	1,000
GSC232	Orange	0.232	0.263	4410	11980	21980-232	1,000
GSC261	Yellow	0.261	0.297	4411	11981	21980-261	1,000
GSC275	Gray	0.275	0.306	4412	11982	21980-275	1,000
GSC281	Purple	0.281	0.331	4414	11984	21980-281	1,000
GSC287	Blue	0.287	0.327	4414	11984	21980-287	1,000
GSC297	Green	0.297	0.335	4414	11984	21980-297	1,000
GSC312	Yellow	0.312	0.362	4415	11985	21980-312	1,000
GSC327	Gray	0.327	0.372	4416	11986	21980-327	1,000
GSC348	Orange	0.348	0.393	4417	11987	21980-348	1,000
GSC359	Purple	0.359	0.399	5450	–	21980-359	1,000
GSC375	Yellow	0.375	0.406	5451	–	21980-375	1,000
GSC405	Red	0.405	0.453	5452	11988	21980-405	1,000
GSC415	Blue	0.415	0.463	5452	11988	21980-415	1,000
GSC425	Gray	0.425	0.475	5454	–	–	1,000
GSC460	Gray	0.460	0.510	5456	–	21980-460	1,000
GSC500	Green	0.500	0.550	5457	–	21980-500	1,000

*Dies 4419 to 4417 are for WT440. Dies 5450 to 5457 are for WT540.
Order multiple is standard package.